

Flexline 6000

The high flexible multispiral compact hydraulic hose with reduced bend radii and bending force meets ISO 18752 – CC and exceeds SAE100 R15



GENERAL

Tube	Synthetic rubber, resistant against hydraulic fluids (HL, HLP, HLPD, HVLP, HFA, HFAS, HFB, HFC) and bio-degradable hydraulic fluids
Reinforcement	Four (4S) or six (6S) high tensile steel wire
Cover	Abrasion and ozone resistant synthetic rubber – MSHA approved Note: MSHA and SemperRock cover available
Temperature range	-40°C to 121°C / -40°F to +250°F
Standard branding	Mylar tape
Note	Impulse tested up to 500.000 cycles [tested acc. to IS6803:2017]

TECHNICAL DETAILS

Nominell			Verstärkungsschichten	Innen-Ø		Spiral-Ø		Außen-Ø		Betriebsdruck [max.]		Min. Berstdruck		Biegeradius [min.]		Gewicht ca.	
mm	Zoll	dash		mm	Zoll	mm	Zoll	mm	Zoll	bar	psi	bar	psi	mm	Zoll	lbs/ft	kg/m
10	3/8	-6	4	9,9	0,39	17,7	0,70	20,2	0,79	420	6090	1680	24360	65	2,6	0,56	0,67
12	1/2	-8	4	13,0	0,51	20,6	0,81	22,9	0,90	420	6090	1680	24360	90	3,5	0,52	0,78
16	5/8	-10	4	16,4	0,65	24,2	0,95	26,5	1,04	420	6090	1680	24360	100	3,9	0,71	1,05
19	3/4	-12	4	19,5	0,77	28,3	1,11	30,5	1,20	420	6090	1680	24360	120	4,7	0,91	1,36
25	1	-16	4	25,9	1,02	35,4	1,39	37,5	1,48	420	6090	1680	24360	150	5,9	1,31	1,95
31	1-1/4	-20	4	32,5	1,28	43,5	1,71	47,3	1,86	420	6090	1680	24360	400	15,7	2,02	3,01
31	1-1/4	-20	6	32,5	1,28	46,9	1,84	50,5	1,99	420	6090	1680	24360	400	15,7	2,53	3,77
38	1-1/2	-24	6	38,7	1,52	53,9	2,12	57,4	2,26	420	6090	1680	24360	460	18,1	3,31	4,93
51	2	-32	6	51,1	2,01	67,9	2,67	71,5	2,81	420	6090	1680	24360	540	21,3	4,63	6,89

Please note: Before using our products with new or untested media, or for applications that are not clearly indicated in the product information, written advice must be obtained from a specialist dealer or a Semperit application engineer. For safety reasons, all products must be inspected regularly for operational safety and replaced in the event of any damage (especially of the cover) or unusual signs of wear and tear. All products must be stored, handled, and maintained in accordance with all our respective instructions and DIN 7716:1982. The information in our catalogue as well as each individual datasheet is subject to change at any time without notice since we are constantly developing and improving our products and due to constant technical developments after the latest release date of the catalogue and/or individual datasheets. In order to always have the latest product and safety information make sure you visit our website (<https://hoses.semperitgroup.com/>) regularly or contact one of our specialist dealers or a Semperit application engineer. All contracts with Semperflex are exclusively subject to our general terms and conditions (available at <https://hoses.semperitgroup.com/>).

Important notice: Our catalogue and any individual datasheet have been prepared with great care in order to provide you with all the information you need. The information contained therein is based on the state-of-the-art industrial technology and many years of experience and testing; whenever indicated for a certain product, we also confirm conformity with the resistance requirements of the media indicated in the product catalogue. However, the individual conditions of storage, maintenance and use decisively affect the safe and durable use of each product. The quality and safety of our products as indicated in the catalogue or individual datasheets are therefore strictly subject to the continuous observance of all specifications and restrictions in our written product information, applicable laws and standards. We reject any liability for safety issues or other consequences due to improper product choice, maintenance, or handling (e.g. squashing, rupturing, stretching or filling with non-approved media). Our products must not be used in airplanes or other aerial vehicles under any circumstance. Unless specified otherwise, all hoses are manufactured according to EN853, 856, 857 and SAE J 517. Our products are not designated for the sale to the general public and do not fulfill the conditions for "GS-certification" (voluntary certification related to tested safety).