


Flexline Plus

The high flexible multi-spiral compact hydraulic hose with reduced bend radii and increased working pressure exceeds performance of EN856 4SP and 4SH



GENERAL

Tube	Synthetic rubber, resistant against hydraulic fluids (HL, HLP, HLPD, HVLP, HFA, HFAS, HFB, HFC) and bio-degradable hydraulic fluids
Reinforcement	Four high tensile steel wire
Cover	Abrasion and ozone resistant synthetic rubber MSHA, SemperRock and SemperShield (DN10-DN25) cover available
Temperature range	-40°C to 100°C / -40°F to +212°F (max 120°C / 248°F intermittent)
Standard branding	Mylar tape
Note	Impulse tested up to 1 million cycles (tested acc. to ISO6803:2017)

TECHNICAL DETAILS

Nominal			Internal-Ø		Spiral-Ø		External-Ø		Work. pressure (max.)		Min. burst pressure		Bending radius (min.)		Weight approx.		Requirements as per EN856 4SP/4SH		
mm	inch	dash	mm	inch	mm	inch	mm	inch	bar	psi	bar	psi	mm	inch	lbs/ft	kg/m	Type	Working Pressure	Bend radius
mm	inch	dash	mm	inch	mm	inch	mm	inch	bar	psi	bar	psi	mm	inch	lbs/ft	kg/m		bar	mm
10	3/8	-6	9.9	0.39	17.7	0.70	20.2	0.79	470	6815	1880	27260	60	2.4	0.46	0.69	Exceeds 4SP	445	180
12	1/2	-8	13.0	0.51	20.6	0.81	22.9	0.90	470	6815	1880	27260	85	3.3	0.53	0.79	Exceeds 4SP	415	230
16	5/8	-10	16.4	0.65	25.0	0.98	27.2	1.07	470	6815	1880	27260	100	3.9	0.79	1.17	Exceeds 4SH	420	200
19	3/4	-12	19.5	0.77	28.3	1.11	30.5	1.20	450	6525	1800	26100	120	4.7	0.91	1.36	Exceeds 4SH	420	280
25	1	-16	25.9	1.02	35.4	1.39	37.5	1.48	440	6380	1760	25520	150	5.9	1.30	1.94	Exceeds 4SH	380	340
31	1-1/4	-20	32.5	1.28	43.5	1.71	47.3	1.86	370	5365	1480	21460	210	8.3	1.81	2.70	Exceeds 4SH	325	460
38	1-1/2	-24	38.7	1.52	49.2	1.94	53.4	2.10	320	4640	1280	18560	250	9.8	2.22	3.31	Exceeds 4SH	290	560
51	2	-32	51.1	2.01	64.3	2.53	68.0	2.68	280	4060	1120	16240	390	15.4	2.97	4.42	Exceeds 4SH	250	700

Please note: Before using our products with new or untested media, or for applications that are not clearly indicated in the product information, written advice must be obtained from a specialist dealer or a Semperit application engineer. For safety reasons, all products must be inspected regularly for operational safety and replaced in the event of any damage [especially of the cover] or unusual signs of wear and tear. All products must be stored, handled, and maintained in accordance with all our respective instructions and DIN 7718:1982. Notwithstanding the above listed temperature range the maximum surface temperature of the SemperShield hose cover must not exceed 120°C. The information in our catalogue as well as each individual datasheet is subject to change at any time without notice since we are constantly developing and improving our products and due to constant technical developments after the latest release date of the catalogue and/or individual datasheets. In order to always have the latest product and safety information make sure you visit our website [hoses.semperitgroup.com] regularly or contact one of our specialist dealers or a Semperit application engineer. All contracts concluded with us are exclusively subject to our general terms and conditions [available at hoses.semperitgroup.com].

Important notice: Our catalogue and any individual datasheet have been prepared with great care in order to provide you with all the information you need. The information contained therein is based on the state-of-the-art industrial technology and many years of experience and testing; whenever indicated for a certain product, we also confirm conformity with the resistance requirements of the media indicated in the product catalogue. However, the individual conditions of storage, maintenance and use decisively affect the safe and durable use of each product. The quality and safety of our products as indicated in the catalogue or individual datasheets are therefore strictly subject to the continuous observance of all specifications and restrictions in our written product information, applicable laws and standards. We reject any liability for safety issues or other consequences due to improper product choice, maintenance, or handling [e.g. squashing, rupturing, stretching or filling with non-approved media]. Our products must not be used in airplanes or other aerial vehicles under any circumstance. Unless specified otherwise, all hoses are manufactured according to EN853, 856, 857 and SAE J 517. Our products are not designated for the sale to the general public and do not fulfill the conditions for "GS-certification" [voluntary certification related to tested safety].