

# FKO

Cooling - NBR - 12 bar



## SPECIFICATIONS

<b>Application</b>	An oil cooling hose for heavy duty use in diesel engines.
<b>Feature</b>	Tube and cover are resistant to oil and fuel.
<b>Temperature range</b>	-35°C / +120°C [oil], +90°C [fuel].
<b>Safety factor</b>	3,15 : 1
<b>Tube</b>	NBR, black, smooth.
<b>Reinforcement</b>	Textile wrapped.
<b>Cover</b>	NBR, black, resistant to oil, cloth impression.
<b>Marking</b>	continuous mylartape, yellow letters: "SEMPERIT [S]".
<b>Notice</b>	ATTENTION: It is vital to be aware of the different working pressures.

## TECHNICAL DETAILS

Article number	Internal-Ø		Wall width	External-Ø	Work. pressure [max.]	Number of inserts	Weight approx.	Coil length [max.]
	mm	inch						
64345 1340	13.0	1/2	4.0	21.0	12	2	0.25	40
64345 1540	15.0		4.0	23.0	12	2	0.30	40
64345 1640	16.0	5/8	4.0	24.0	12	2	0.30	40
64345 2040	20.0		4.0	28.0	12	2	0.40	40
64345 2240	22.0	7/8	4.0	30.0	12	2	0.40	40
64345 2540	25.0	1	4.0	33.0	12	2	0.45	40
64345 3040	30.0	1 3/16	4.0	38.0	12	2	0.50	40
64345 3240	32.0	1 1/4	4.0	40.0	12	2	0.55	40
64345 3540	35.0	1 3/8	4.0	43.0	12	2	0.60	40
64345 3840	38.0	1 1/2	4.0	46.0	12	2	0.65	40
64345 4040	40.0		4.0	48.0	12	2	0.80	40
64345 4245	42.0		4.5	51.0	8	2	0.80	40
64345 4545	45.0		4.5	54.0	8	2	0.85	40
64345 5045	50.0		4.5	59.0	8	2	0.90	40
64345 5545	55.0		4.5	64.0	8	2	1.00	40
64345 6050	60.0		5.0	70.0	8	2	1.20	40
64345 7050	70.0		5.0	80.0	8	2	1.40	40

**Please note:** Before using our products with new or untested media, or for applications that are not clearly indicated in the product information, written advice must be obtained from a specialist dealer or a Semperit application engineer. For safety reasons, all products must be inspected regularly for operational safety and replaced in the event of any damage (especially of the cover) or unusual signs of wear and tear. All products must be stored, handled, and maintained in accordance with all our respective instructions and DIN 7716:1982. The information in our catalogue as well as each individual datasheet is subject to change at

any time without notice since we are constantly developing and improving our products and due to constant technical developments after the latest release date of the catalogue and/or individual datasheets. To always have the latest product and safety information make sure you visit our website [hoses.semperitgroup.com] regularly or contact one of our specialist dealers or a Semperit application engineer. All contracts concluded with us are exclusively subject to our general terms and conditions [available at semperitgroup.com]. Additional important general information about the range, choice and safe use of our products can be found at our website [hoses.semperitgroup.com] and must be followed without exception.

**Important notice:** Our catalogue and any individual datasheet have been prepared with great care in order to provide you with all the information you need. The information contained therein is based on the state-of-the-art industrial technology and many years of experience and testing; whenever indicated for a certain product, we also confirm conformity with the resistance requirements of the media listed in ISO TR 7620:2005[E]. However, the individual conditions of storage, maintenance and use decisively affect the safe and durable use of each product. The quality and safety of our products as indicated in the catalogue or individual datasheets are therefore strictly subject to your continuous observance of all specifications and restrictions in our written product information and applicable laws and standards, the specifications regarding resistance to chemicals and our cleaning procedures. We reject any liability for safety issues or other consequences due to improper product choice, maintenance, or handling (e.g. squashing, rupturing, stretching, or filling with non-approved media). Our products must not be used in airplanes or other aerial vehicles under any circumstance. Products delivered by us to the USA are manufactured according to ARPM-IP2, unless specified otherwise. All other hoses are manufactured according to EN ISO 1307:2008, unless specified otherwise. Our products are not designated for the sale to the general public and do not fulfill the conditions for "GS-certification", unless stated otherwise in the product datasheet.