

FPB

Propan/Butan - NBR - 4,5 bar - D



SPECIFICATIONS

Application	Flexible Hose suitable for low pressure delivery of propane- butane gas (LPG) as part of the propulsion system in vehicles.					
Feature	The FPB product can be used with LPG (Liquified Petroleum Gas) only. Not recommended for use with CNG (Compressed Natural Gas). The material properties might be affected and weakened during usage					
Temperature range	-40°C/+85°C.					
Safety factor	4:1					
Tube	NBR, black, smooth.					
Reinforcement	Textile spiral.					
Cover	SBR/EPDM, black, smooth.					
Marking	continuous inkjet, white letters: "SEMPERIT (S) FPB LPG PN 4,5 bar DN XQ/YYYY MADE IN EU //////".					
Notice	The usage of our product is only allowed for land and sea applications. ATTENTION: For last valid information regarding oil & fuel suitability please always refer to the Semperit oil & fuel suitability matrix or, in case of doubt, contact Semperit. ATTENTION: Not to be used as a petrol pump hose.					

TECHNICAL DETAILS

				0	$\textcircled{\textbf{S}}$		(\frown)	$\widehat{\square}$	<u>II</u>
Article number	Internal-Ø		Wall width	External-Ø	Work. pressure (max.)	Number of inserts	Bending radius (min.)	Weight approx.	Coil length (max.)
	mm	inch	mm	mm	bar		mm	kg/m	m
68032 0630	6.0		3.0	12.0	4.5	2	40	0.11	50
68032 1235	12.0		3.5	19.0	4.5	2	70	0.23	50
68032 1335	13.0	1/2	3.5	20.0	4.5	2	80	0.25	50
68032 1640	16.0	5/8	4.0	24.0	4.5	2	100	0.34	50
68032 1945	19.0	3/4	4.5	28.0	4.5	2	120	0.40	50

Please note: Before using our products with new or untested media, or for applications that are not clearly indicated in the product information, written advice must be obtained from a specialist dealer or a Semperit application engineer. For safety reasons, all products must be inspected regularly for operational safety and replaced in the event of any damage (especially of the cover) or unusual signs of wear and tear. All products must be stored, handled, and maintained in accordance with all our respective instructions and DIN 7716:1982. The information in our catalogue as well as each individual datasheet is subject to change at any time without notice since we are constantly developing and improving our products and us to constant technical developments after the latest release date of the catalogue and/or individual datasheets. To always have the latest product and safety information make sure you visit our website (hoses.semperitgroup.com). Additional important general information about the range, choice and safe use of our products can be found a tour website (hoses.semperitgroup.com) and must be followed without exception.

Important notice: Our catalogue and any individual datasheet have been prepared with great care in order to provide you with all the information you need. The information contained therein is based on the state-ofthe-art industrial technology and many years of experience and testing; whenever indicated for a certain product, we also confirm conformity with the resistance requirements of the media listed in ISO TR 7620:2005[E]. However, the individual conditions of storage, maintenance and use decisively affect the safe and durable use of each product. The quality and safety of our products as indicated in the catalogue or individual datasheets are therefore strictly subject to your continuous observance of all specifications in our written product information and applicable laws and standards, the specifications regarding resistance to chemicals and our cleaning procedures. We reject any liability for safety issues or other consequences due to improper product choice, maintenance, or handling [e.g. squashing, rupturing, stretching, or filling with non-approved media). Our products must not be used in airplanes or other aerial vehicles under any circumstance. Products delivered by us to the USA are manufactured according to IRPM-IP2, unless specified otherwise. All other hoses are manufactured according to EN ISO 1307:2008, unless specified otherwise. Our products are not designated for the sale to the general public and do not fulfill the conditions for "GS-certification", unless stated otherwise in the product datasheet.