

DHH










Hot water - EPDM - 10 bar - D



SPECIFICATIONS

Application	A flexible hose for conveying hot water for many applications in industry. Suitable for transporting anti-freezing agents in cars, tractors and trucks.
Temperature range	-45°C / +120°C. max. +100°C fluid temperature in closed systems.
Safety factor	5 : 1
Tube	EPDM, black, smooth.
Reinforcement	Textile wrapped.
Cover	EPDM, black, resistant to ozone and weather, cloth impression.
Marking	embossed tape: "SEMPERIT (S) DHH HOT WATER WP 10 BAR / +100°C [conditionally +120°C] MADE IN EU".
Notice	<p>ATTENTION: Hot water hose is not suitable for steam applications, (for steam use we recommend DS1 ultra, DS2, DS3).</p> <p>ATTENTION: As temperature increases or decreases, burst pressure, safe working pressure, coupling retention properties and other safety characteristics of the hose can significantly decrease in closed systems/applications. Failure to consider how temperature and other conditions affect hose performance may cause property damage, serious bodily injury or death. The hose must not be used in constantly pressurized closed systems at temperatures >100°C.</p> <p>ATTENTION: The temperature of the medium must be lower than its boiling point.</p>

TECHNICAL DETAILS

<div></div>									
Article number	Internal-Ø		Wall width	External-Ø	Work. pressure [max.]	Number of inserts	Bending radius [min.]	Weight approx.	Coil length [max.]
	mm	inch	mm	mm	bar		mm	kg/m	m
48444 1350	13.0	1/2	5.0	23.0	10	2	50	0.35	40
48444 1650	16.0	5/8	5.0	26.0	10	2	80	0.40	40
48444 1945	19.0	3/4	4.5	28.0	10	2	110	0.45	40
48444 1950	19.0	3/4	5.0	29.0	10	2	100	0.50	40
48444 2550	25.0	1	5.0	35.0	10	2	125	0.60	40
48444 2555	25.0	1	5.5	36.0	10	2	125	0.65	40
48444 3260	32.0	1 1/4	6.0	44.0	10	2	150	0.80	40
48444 3860	38.0	1 1/2	6.0	50.0	10	2	190	1.05	40
48444 5080	50.0		8.0	66.0	10	4	220	1.70	40
48444 5175	51.0	2	7.5	66.0	10	4	223	1.65	40
48444 6375	63.5	2 1/2	7.5	78.5	10	4	270	1.95	40
64444 7680	76.0	3	8.0	92.0	10	4	310	2.50	40
64444 1010	102.0	4	10.0	122.0	10	4	370	4.30	40

Please note: Before using our products with new or untested media, or for applications that are not clearly indicated in the product information, written advice must be obtained from a specialist dealer or a Semperit application engineer. For safety reasons, all products must be inspected regularly for operational safety and replaced in the event of any damage [especially of the cover] or unusual signs of wear and tear. All products must be stored, handled, and maintained in accordance with all our respective instructions and DIN 7716:1982. The information in our catalogue as well as each individual datasheet is subject to change at any time without notice since we are constantly developing and improving our products and due to constant technical developments after the latest release date of the catalogue and/or individual datasheets. To always have the latest product and safety information make sure you visit our website [hoses.semperitgroup.com] regularly or contact one of our specialist dealers or a Semperit application engineer. All contracts concluded with us are exclusively subject to our general terms and conditions [available at semperitgroup.com]. Additional important general information about the range, choice and safe use of our products can be found at our website [hoses.semperitgroup.com] and must be followed without exception.

Important notice: Our catalogue and any individual datasheet have been prepared with great care in order to provide you with all the information you need. The information contained therein is based on the state-of-the-art industrial technology and many years of experience and testing; whenever indicated for a certain product, we also confirm conformity with the resistance requirements of the media listed in ISO TR 7620:2005(E). However, the individual conditions of storage, maintenance and use decisively affect the safe and durable use of each product. The quality and safety of our products as indicated in the catalogue or individual datasheets are therefore strictly subject to your continuous observance of all specifications and restrictions in our written product information and applicable laws and standards, the specifications regarding resistance to chemicals and our cleaning procedures. We reject any liability for safety issues or other consequences due to improper product choice, maintenance, or handling [e.g. squashing, rupturing, stretching, or filling with non-approved media]. Our products must not be used in airplanes or other aerial vehicles under any circumstance. Products delivered by us to the USA are manufactured according to IRPM-IP2, unless specified otherwise. All other hoses are manufactured according to EN ISO 1307:2008, unless specified otherwise. Our products are not designated for the sale to the general public and do not fulfill the conditions for "GS-certification", unless stated otherwise in the product datasheet.